



# CoverClean AE

Deep cleaning, advanced ecofriendly microbial cleaner for grout and tile

## Product Description

CoverClean AE is a professional grade floor cleaning solution that uses micro-organisms to digest and clean dirt, grease and urea from hard tile and grout surfaces. This advanced eco-friendly product has been especially developed for the deep cleaning oils, urine, heavy odors, soap scum, sun tan lotion, pet stains and other organic matter from tile and grout, stone wood and laminate flooring.

CoverClean AE is environmentally safe, USDA compliant and harmless to humans, pets, plants and aquatic life.

## Features

- Eliminates heavy oil and grease contaminants
- Rapidly consumes odor causing bacteria
- Digests oil and grease rather than dispersing them
- Leaves no residue
- Greatly increases slip resistance
- Leaves room clean smelling
- Non-exposure to hazardous chemicals
- Cleans all surfaces
- Meets USDA requirements
- Cleans pores in grout
- Fast acting
- Non-flammable
- No VOC's
- Cleans without polluting
- 

## Main Uses

- Cleaning Heavy Grease and Oils
- Removing urea and odor casing bacteria
- Soap scum and tanning oils
- Quarry Tile and Grout
- Public Restrooms
- Health Clubs
- Changing Rooms
- Walls and floors
- Any Hard Surface
- Wood and Laminate
- Counters, Sinks and Plumbing
- Country Clubs
- Restaurants and Hotels

## Packaging

1 quart (0.95L), 1 gallon (3.78L) and 5 gallon (19L) pail

## Shelf Life

12 months when stored at 77°F (25°C) or less in a dry and shaded area. Protect from freezing

## Installation Guidelines

### Application

For everyday cleaning add 2-3 oz. to a gallon of water and apply by either a mop, spray or cloth. Allow solution to dwell on the surface for 2-3 minutes then wipe off with a clean cloth.

For heavy duty cleaning, apply undiluted by spray or mop directly to the affected area. Apply generously and scrub with brush until area is covered. Make sure the cleaner is scrubbed well into the grout lines. Wait 5-10 minutes then pick up soil and any excess solution with a damp mop, towel, or squeegee towards a floor drain. This will help keep drains clean from grease, oil and soap scum.

Allow floor to air dry before reuse. No Rinsing required.

Do not allow solution temperature to rise above 120°F (48.9°C)

For specific cleaning applications, please contact CoverTec Technical Service at [tec@covertecproducts.com](mailto:tec@covertecproducts.com)

## Limitations

Do not allow product to freeze

Do not on substrates at temperature above 120°F (48.9°C)

Do not use on substrates at temperature below 40°F (5°C)

Do not store product at temperatures above 120°F (48.9°C)

Test area to determine cleaning time and coverage.

**Health and Safety**

**Before using this product consult the Material Safety Data Sheet (MSDS). The MSDS can be obtained at [www.covertecproducts.com](http://www.covertecproducts.com)**

**Limited Warranty**

This product is warranted to be of good quality and that it complies with the properties shown in its current datasheet. CoverTec will replace or, at our election, refund the purchase price of the product if proven defective when used according to the instructions in the current datasheet. Any suspected defect must be reported to CoverTec in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. CoverTec Products LLC, **makes no warranty as to the merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied and explicitly excludes liability for consequential damages, down time, or delay.**